



## FIRE RESISTANT ENCLOSURES



### vital as...

Protect property and people  
For safe, clean and green living  
AS/NZS 3000:2007 compliant  
Allows insulation to be effective!



### easy as...

Fit from below the ceiling  
For existing or new downlights  
Sides can abut timber & insulation  
Full instructions supplied



### tough as...

Made of fireproof fibreglass  
Ideal upper floor protection  
Independently tested by ITACS  
Approval No. A/10460E

## Flexi™ DLC & FRE models suit

- ✓ Limited access areas e.g. between floors, skillion roofs, cathedral ceilings, under hanging beams, etc.
- ✓ 12V downlights (240V - use VENTED DLC0 size or larger)
- ✓ Most downlight sizes\* (*Flexi™ can be made to order*)

NOTES: Enquire about our "fit from above ceiling" models

*\*Equipment used with Flexi™ is a variable beyond Arrowform's control. The customer is responsible to select quality light fittings &/ or combinations. Comply with all Flexi™ Installation Instructions. Common uses (C.U.) indicated for each Flexi™ model are given as a guide only. Lighting enclosures should not exceed the maximum surface temperatures of AS/NZS 60598 for zero clearance use. This should be considered when any globe exceeds 50W (or 35W max for energy saver halogen globes).*

## Why choose Flexi™ Downlight Enclosures?

- ✓ Easy compliance to AS/NZS3000:2007 clause 4.5.2.3 (b) Approval No. A/10460E. Full instructions supplied.
- ✓ Prevent common downlight ceiling fire devastation. Smoke alarms and insurance cover don't do this!
- ✓ Safe-touch ENCLOSURE around ignition temp. globe. Vital peace of mind... Complete protection against common future fire risk e.g. loose insulation, leaves, nests, pests, debris, as required by the Standard etc.
- ✓ When above ceiling access is not practical.



- ✓ Avoid severe positioning limitations, choose flexibility. Enclosure has instructions to abut timber & insulation.
- ✓ Prevent loss of vital thermal and acoustic insulation cover and benefits. Allows optimum cover and effectiveness.
- ✓ Fully enclose the 12V/240V downlight (or bank of downlights) of your choice.
- ✓ Close up 24/7 downlight openings between living area and dusty, allergen-laden ceiling for a safe, clean, healthy, green indoors. For best results use FRE unvented models.



For sales and stockist enquiries



Engineered Products for the future

FRECALL 1800 852 741

Fax 1300 722 165

Email: sales@arrowform.com.au

www.arrowform.com.au



## FLEXIBLE FIRE RESISTANT DOWNLIGHT ENCLOSURES



*fit from below!*

Proven  
Approved  
Flexi-Fit  
Easy



PREVENT  
CONSEQUENCES  
NO-ONE  
CAN AFFORD!





## COOL FIRE RESISTANT DOWNLIGHT ENCLOSURES

✓ **DLC1**  
Flexi™ Downlight Cover  
130 x 130 x 70mm HIGH!  
Note: FRE1 not available  
(C.U.\*: 12V halogen)

✓ **FRE2 / DLC2**  
Flexi™ Downlight Cover  
130 x 130 x 100mm H  
(C.U.\*: 12V halogen)

✓ **FRE0 / DLC0 / DLC0AC\***  
Flexi™ Downlight Cover  
150 x 150 x 130mm H  
(C.U.\*: 12V halogen, 240V halogen/CFL - use vented DLCO. Enquire re CFL/FRE0 use)  
**\*Rw38 ACOUSTIC VERSION**

✓ **FRE3 / DLC3**  
Flexi™ Downlight Cover  
270 x 160 x 100mm H  
(C.U.\*: Bank of 2 x 12V halogens)

✓ **FRE4 / DLC4**  
Flexi™ Downlight Cover  
180 x 180 x 130mm H  
(C.U.\*: Wide 240V CFL)

✓ **FRE5 / DLC5**  
Flexi™ Downlight Cover  
180 x 180 x 170mm H  
(C.U.\*: Tall 240V CFL)

✓ **FRE6 / DLC6**  
Flexi™ Downlight Cover  
250 x 250 x 130mm H  
(C.U.\*: 240V Shoplighter)

✓ **FRE8 / DLC8**  
Flexi™ Downlight Cover  
300 x 300 x 170mm H  
(C.U.\*: Square bank of 4 x 12V halogens)

✓ **FRE9 / DLC9**  
Flexi™ Downlight Cover  
350 x 350 x 230mm H  
(C.U.\*: Square bank of 4 x 12V halogens)

✓ **FRE10 / DLC10**  
Flexi™ Downlight Cover  
220 x 220 x 260mm H  
(C.U.\*: 240V Incandescent, or Heat lamp [NOT fan/ lights!])

✓ **FRE11 / DLC11**  
Flexi™ Downlight Cover  
380 x 170 x 170mm H  
(C.U.\*: Bank of 3 x 12V halogens)



FIT FROM BELOW!



ZERO CLEARANCE

Fireproof fibreglass enclosures. Ideal approved protection for upper floors, commercial ceilings, etc. Unvented FRE models provide best installation convenience and indoor pollution/energy loss prevention. Flexi™ also allows optimum energy saving insulation effectiveness.

NOTE: Flexi™ product dimensions and cable entry specifications may vary without notice

Standard Flexi™ model accessories; The first 3 sizes have 1 wire frame and 2 locating thumb clips. Larger sizes have 2 frames and 4 clips



FRE models cable entry



INSIDE FLEXI™



DLC models cable entry

\*C.U. = Common Use

Flexi™ ... Fast, Fireproof...

Get Genuine ENCLOSURE