



FIRE RESISTANT ENCLOSURES



vital as...

Protect property and people
For safe, clean and green living
AS/NZS 3000:2007 compliant
Allows insulation to be effective!



easy as...

Fit from below the ceiling
For existing or new downlights
Sides can abut timber & insulation
Full instructions supplied



tough as...

Made of fireproof fibreglass
Ideal upper floor protection
Independently tested by ITACS
Approval No. A/10460E

Flexi™ DLC & FRE models suit

- ✓ Limited access areas e.g. between floors, skillion roofs, cathedral ceilings, under hanging beams, etc.
- ✓ 12V downlights (240V - use VENTED DLC0 size or larger)
- ✓ Most downlight sizes* (*Flexi™ can be made to order*)

NOTES: Enquire about our "fit from above ceiling" models

**Equipment used with Flexi™ is a variable beyond Arrowform's control. The customer is responsible to select quality light fittings &/ or combinations. Comply with all Flexi™ Installation Instructions. Common uses (C.U.) indicated for each Flexi™ model are given as a guide only. Lighting enclosures should not exceed the maximum surface temperatures of AS/NZS 60598 for zero clearance use. This should be considered when any globe exceeds 50W (or 35W max for energy saver halogen globes).*

Why choose Flexi™ Downlight Enclosures?

- ✓ Easy compliance to AS/NZS3000:2007 clause 4.5.2.3 (b) Approval No. A/10460E. Full instructions supplied.
- ✓ Prevent common downlight ceiling fire devastation. Smoke alarms and insurance cover don't do this!
- ✓ Safe-touch ENCLOSURE around ignition temp. globe. Vital peace of mind... Complete protection against common future fire risk e.g. loose insulation, leaves, nests, pests, debris, as required by the Standard etc.
- ✓ When above ceiling access is not practical.



- ✓ Avoid severe positioning limitations, choose flexibility. Enclosure has instructions to abut timber & insulation.
- ✓ Prevent loss of vital thermal and acoustic insulation cover and benefits. Allows optimum cover and effectiveness.
- ✓ Fully enclose the 12V/240V downlight (or bank of downlights) of your choice.
- ✓ Close up 24/7 downlight openings between living area and dusty, allergen-laden ceiling for a safe, clean, healthy, green indoors. For best results use FRE unvented models.
- ✓ Fireproof enclosures. DLC models fire-rated for 60 minutes to BS476 (vented intumescent cable entry).

For sales and stockist enquiries

ARROWFORM

Engineered Products for the future

FRECALL 1800 852 741

Fax 1300 722 165

Email: sales@arrowform.com.au

www.arrowform.com.au



FLEXIBLE FIRE RESISTANT DOWNLIGHT ENCLOSURES



fit from below!

Proven
Approved
Flexi-Fit
Easy



PREVENT
CONSEQUENCES
NO-ONE
CAN AFFORD!





COOL FIRE RESISTANT DOWNLIGHT ENCLOSURES

✓ **DLC1**
Flexi™ Downlight Cover
130 x 130 x 70mm HIGH!
*Note: FRE1 not available
(C.U.*: 12V halogen)*

✓ **FRE2 / DLC2**
Flexi™ Downlight Cover
130 x 130 x 100mm H
(C.U.: 12V halogen)*

✓ **FRE0 / DLC0 / DLC0AC***
Flexi™ Downlight Cover
150 x 150 x 130mm H
(C.U.: 12V halogen, 240V
halogen/CFL - use vented DLCO.
Enquire re CFL/FRE0 use)*
***Rw38 ACOUSTIC VERSION**

✓ **FRE3 / DLC3**
Flexi™ Downlight Cover
270 x 160 x 100mm H
(C.U.: Bank of 2 x 12V halogens)*

✓ **FRE4 / DLC4**
Flexi™ Downlight
Cover
180 x 180 x 130mm H
(C.U.: Wide 240V CFL)*

✓ **FRE5 / DLC5**
Flexi™ Downlight Cover
180 x 180 x 170mm H
(C.U.: Tall 240V CFL)*

✓ **FRE6 / DLC6**
Flexi™ Downlight Cover
250 x 250 x 130mm H
(C.U.: 240V Shoplighter)*

✓ **FRE8 / DLC8**
Flexi™ Downlight Cover
300 x 300 x 170mm H
(C.U.: Square bank of 4 x
12V halogens)*

✓ **FRE9 / DLC9**
Flexi™ Downlight Cover
350 x 350 x 230mm H
(C.U.: Square bank of 4 x 12V
halogens)*

✓ **FRE10 / DLC10**
Flexi™ Downlight Cover
220 x 220 x 260mm H
(C.U.: 240V Incandescent,
or Heat lamp
[NOT fan/ lights])*

✓ **FRE11 / DLC11**
Flexi™ Downlight Cover
380 x 170 x 170mm H
(C.U.: Bank of 3 x 12V halogens)*



FIT FROM BELOW!



ZERO CLEARANCE

Fireproof fibreglass enclosures. Ideal approved protection for upper floors, commercial ceilings, etc. Vented intumescent DLC models are fire rated for 60 minutes. Unvented FRE models provide best installation convenience and indoor pollution/energy loss prevention. Flexi™ also allows optimum energy saving insulation effectiveness.

NOTE: Flexi™ product dimensions and cable entry specifications may vary without notice

Standard Flexi™ model accessories;
The first 3 sizes have 1 wire frame and 2 locating
thumb clips. Larger sizes have 2 frames and 4 clips



FRE models cable entry



INSIDE FLEXI™



DLC models cable entry

*C.U. = Common Use

Flexi™ ... Fast, Fireproof...

Genuine ENCLOSURES